

# MONRO-JET F4

MONRO-JET® nozzles combine the high power of the point jet with the large area output of the flat jet. They can be used with all approved high-pressure fittings and mounted on lances.


The model F4 can be used up to an operating pressure of 500 bar, and five different connection thread types are available. Due to their compact design, MONRO-JET® nozzles can be used both in building construction and in civil engineering for surface treatment and cleaning.

## PROPERTIES AND ADVANTAGES

- SWISS QUALITY
- HIGHER CLEANING CAPACITY LEVELS
- CONSTANT JET QUALITY
- LONG LIFETIME
- LIGHT, DURABLE AND RELIABLE
- EASY TO INSTALL AND DISASSEMBLE

## APPLICATIONS

- REMOVAL OF BITUMEN LAYERS
- SURFACE TREATMENT
- REMOVAL OF SURFACE COATINGS
- PAINT REMOVAL



CHARACTERISTICS	TYPE
	MONRO JET F4
Operating pressure (bar)	max. 500
Operating temp. (°C)	max. 100°
Rotor Ø (mm)	from 0.60 to 2.80

Jan van der Heijdenstraat 44  
3261 LE Oud-Beijerland  
The Netherlands

T +31 186 62 14 84  
info@salotech.nl  
www.salotech.nl

ROTOR Ø	DRIVING TUBS Ø	NUMBER OF BORLS	PRESSURE IN PSI / BAR	
			psi 2900	psi /250
			bar 200	bar 500
FLOW RATE IN L/MIN				
0.60	0.60	2	2.849	4.482
0.65	0.65	2	3.320	5.235
0.70	0.70	2	3.400	5.348
0.75	0.70	2	3.719	5.990
0.80	0.70	2	4.711	7.354
0.85	0.70	2	5.054	7.950
0.90	0.70	2	6.305	9.916
0.95	1.00	2	6.788	10.676
1.00	1.00	2	7.971	12.537
1.05	1.20	2	8.617	13.546
1.10	1.40	2	9.804	15.420
1.15	1.40	2	10.410	16.385
1.20	1.80	2	12.010	18.903
1.25	1.80	2	13.143	20.673
1.30	2.40	2	14.263	22.434
1.35	2.40	2	15.609	24.677
1.40	2.40	2	16.910	26.597
1.45	2.60	2	18.238	28.685
1.50	2.60	2	19.517	30.698
1.55	2.80	2	20.840	32.779
1.60	2.80	2	22.206	34.927
1.65	3.00	2	23.616	37.144
1.70	3.00	2	25.069	39.430
1.75	3.00	2	26.565	41.783
1.80	3.20	2	28.105	44.205
1.85	3.20	2	29.680	46.695
1.90	3.20	2	31.314	49.253
1.95	3.20	2	32.984	51.879
2.00	3.00	4	34.697	54.574
2.05	3.00	4	36.454	57.337
2.10	3.00	4	38.254	60.168
2.15	3.20	4	40.097	63.067
2.20	3.20	4	41.984	66.035
2.25	3.20	4	43.914	69.070
2.30	3.20	4	45.887	72.174
2.35	3.20	4	47.904	75.346
2.40	3.20	4	49.964	78.587
2.45	3.20	4	52.067	81.895
2.50	3.20	4	54.214	85.272
2.55	3.50	4	56.404	88.717
2.60	3.50	4	58.638	92.230
2.65	3.50	4	60.915	95.812
2.70	3.50	4	63.235	99.461
2.75	3.50	4	65.599	103.179
2.80	3.50	4	68.006	106.965

	< 150 N
	< 250 N
	> 250 N