



PRODUKT CATALOGUE WATERBLAST

S* Product Overview

SPIR STAR®

HIGH PRESSURE PERFORMANCE

COMPANY

SPIR STAR[®] AG is an international leader in the manufacture of thermoplastic ultra-high-pressure hoses with spiralized reinforcement made of steel wire suitable for pressures ranging from 250 bar to 4,000 bar (3,600 psi to 58,000 psi) and with inner diameters ranging from 3 mm to 32 mm.

As a full-range and reliable partner in ultra-high-pressure applications, SPIR STAR[®] completes its product portfolio by high-pressure valves, fittings, tubing and couplers. Thanks to the company's premium-quality products combined with outstanding customer service, SPIR STAR[®] is firmly established in the industrial segments of water blasting, hydraulics, hydrogen, oil & gas and the automotive industry.


Product solutions in the waterjet industry require safe, robust and durable hose assemblies. With our wide range of products, we have been a reliable and essential partner for our customers for decades. A wide range of hose types and connections is available for the complex and demanding applications that arise in the industry. Our innovative developments offer the right waterjet hose for every purpose.

APPLICATIONS


TUBE CLEANING




TANK CLEANING



SURFACE- PREPARATION



CUTTING AND DEMOLITION



DuraLife Flex[®] – Long service life

The approved and tested DuraLife Flex[®] high-tech hose is the ideal hose to use in pipe cleaning applications. Its special manufacturing process greatly reduces abrasion of the cover, thus increasing the service life of the hose assembly.

Hose types: 4/2, 4/2H-1400, 4/4UHP-X-3035, 5/2, 5/2H-1400, 5/3, 6/2, 6/2-1100, 6/3, 8/2 und 8/2-1000.

Ultra-High-Pressure – The water-blast hose for maximum pressure

The hose types of the UHP[®]-Series (Ultra-High-Pressure) are used up to 4.000 bar (58,000 psi). High-pressure combined with a maximum flow rate ensures a fast and optimum cleaning result.

Hose types: 4/4UHP-X-3035, 5/6UHP-X-3035, 5mmUHP, 5mmUHP-X, 6mmUHP, 8/6UHP, 8/6UHP-X, 8mmUHP, 10mmUHP-X-3035, 13mmUHP, 16mmUHP.

Double Cover — Double protection for extended service life

A second cover is an abrasive protection and support a longer service life. In comparison to PVC cover all DC-hose assemblies are lighter and could be delivered in longer lengths.



Product Overview - Waterblasting

HIGH PRESSURE PERFORMANCE

Type	Hose Size				Pressure Rating				Bend Radius		Weight		Insert ID		Sleeve OD	
	ID		OD		Working		Burst		[mm]	[in]	[kg/m]	[lbs/ft]	[mm]		[in]	
	[mm]	[in]	[mm]	[in]	[bar]	[psi]	[bar]	[psi]					[mm]	[in]	[mm]	[in]

Tube Cleaning up to 1.200 bar / 17.400 psi

Application: Heat exchanger tube cleaning, cleaning with automated rigid lances, flex lances or manual rigid lances

3/2	3,4	0,13	6,9	0,27	1.000	14.500	2.500	36.250	60	2,36	0,072	0,048	2,0	0,08	8,9	0,35
3/2-1100	3,4	0,13	7,0	0,28	1.100	15.950	2.750	39.875	60	2,36	0,072	0,048	2,0	0,08	8,9	0,35
4/2	4,0	0,16	8,0	0,31	1.200	17.400	3.000	43.500	75	2,95	0,110	0,074	2,5	0,10	10,1	0,39
5/2	5,0	0,20	9,4	0,37	1.040	15.080	2.600	37.700	95	3,74	0,125	0,084	3,0	0,12	12,9	0,50
5/3	5,0	0,20	10,3	0,41	1.120	16.240	2.800	40.600	95	3,74	0,218	0,146	3,0	0,12	12,9	0,50
6/2	6,3	0,25	11,5	0,45	1.000	14.500	2.500	36.250	110	4,33	0,175	0,117	4,0	0,16	13,9	0,54
6/2-1100	6,3	0,25	11,6	0,46	1.100	15.950	2.750	39.875	110	4,33	0,175	0,117	4,0	0,16	13,9	0,54
6/3	6,1	0,24	12,3	0,48	1.040	15.080	2.600	37.700	110	4,33	0,280	0,188	4,0	0,16	14,1	0,55
8/2	8,1	0,32	13,3	0,52	900	13.050	2.250	32.625	130	5,12	0,200	0,134	5,5	0,22	17,8	0,70
8/2-1000	8,1	0,32	13,3	0,52	1.000	14.500	2.500	36.250	110	4,33	0,200	0,134	5,5	0,22	17,8	0,70
10/2	10,1	0,40	15,5	0,61	690	10.005	1.725	25.010	160	6,30	0,280	0,188	6,5	0,26	20,8	0,81
13/2	12,9	0,51	19,3	0,76	690	10.005	1.725	25.010	200	7,87	0,435	0,291	8,5	0,33	26,0	1,02
16/4	16,0	0,63	25,5	1,00	1.040	15.080	2.600	37.700	250	9,84	1,002	0,671	10,5	0,41	32,7	1,28
20/2	19,0	0,75	26,2	1,03	520	7.540	1.300	18.850	240	9,45	0,750	0,503	13,0	0,51	34,2	1,34
20/4	18,8	0,74	28,8	1,13	1.040	15.080	2.600	37.700	250	9,84	1,350	0,905	13,0	0,51	36,9	1,45
25/2	24,8	0,98	33,5	1,32	440	6.380	1.100	15.950	300	11,81	0,950	0,636	16,5	0,65	40,0	1,57
25/4	24,8	0,98	36,3	1,43	900	13.050	2.250	32.625	300	11,81	1,715	1,149	19,0	0,75	45,9	1,80
8/4HW-1000	8,0	0,31	14,6	0,57	1.000	14.500	3.800	55.100	200	7,87	0,390	0,261	4,5	0,18	20,3	0,79

Tube Cleaning up to 2.200 bar / 32.000 psi

Application: Heat exchanger tube cleaning, cleaning with automated rigid lances, flex lances or manual rigid lances

4/2H-1400	4,0	0,16	8,1	0,32	1.400	20.300	3.500	50.750	75	2,95	0,112	0,075	2,5	0,10	10,1	0,39
4/4	4,0	0,16	10,3	0,41	2.200	31.900	5.500	79.750	130	5,12	0,234	0,157	1,8	0,07	14,7	0,57
5/2H-1400	4,9	0,19	9,5	0,37	1.400	20.300	3.500	50.750	95	3,74	0,148	0,099	3,0	0,12	12,9	0,50
5/4	5,0	0,20	11,2	0,44	1.800	26.100	4.500	65.250	150	5,91	0,260	0,174	2,5	0,10	15,0	0,59
6/4	6,3	0,25	12,6	0,50	1.500	21.750	3.800	55.100	180	7,09	0,295	0,198	3,5	0,14	16,4	0,64
6/4-1650	6,3	0,25	12,6	0,50	1.650	23.925	4.125	59.812	180	7,09	0,295	0,198	3,5	0,14	16,4	0,64
8/4	8,0	0,31	14,6	0,57	1.500	21.750	3.800	55.100	200	7,87	0,390	0,261	4,5	0,18	20,3	0,79
13/4H	12,8	0,50	22,0	0,87	1.400	20.300	3.500	50.750	200	7,87	0,880	0,590	7,5	0,30	29,5	1,16

Tube Cleaning up to 3.050 bar / 44.000 psi

Application: Heat exchanger tube cleaning, cleaning with automated rigid lances, flex lances or manual rigid lances

3/6	3,0	0,12	9,1	0,36	2.800	40.600	7.000	101.500	150	5,91	0,222	0,149	1,8	0,07	15,3	0,60
4/6	4,0	0,16	11,5	0,45	2.800	40.600	7.000	101.500	175	6,89	0,365	0,245	1,8	0,07	17,1	0,67
4/4UHP-X-3035	4,0	0,16	9,9	0,39	3.035	44.000	6.100	88.450	90	3,54	0,234	0,157	2,5	0,10	14,7	0,58
5/6	4,8	0,19	13,2	0,52	2.500	36.250	6.250	90.625	200	7,87	0,450	0,302	2,5	0,10	17,8	0,70
5/6H	4,6	0,18	14,4	0,57	2.800	40.600	7.000	101.500	220	8,66	0,563	0,377	2,5	0,10	17,9	0,70
5/6HDCI	4,6	0,18	18,4	0,72	2.800	40.600	7.000	101.500	220	8,66	0,687	0,460	2,5	0,10	17,9	0,70
5/6UHP-X-3035	4,8	0,19	13,3	0,52	3.035	44.000	7.000	101.500	210	8,27	0,450	0,302	2,5	0,10	17,8	0,91
8/6UHP	7,6	0,30	19,3	0,76	2.800	40.600	7.000	101.500	300	11,81	1,055	0,707	4,5	0,18	23,7	0,93
13mmUHP	12,8	0,50	27,7	1,09	2.800	40.600	6.000	87.000	350	13,78	2,085	1,397	7,5	0,30	34,6	1,36

ONEPIECE FITTINGS® END-FITTING



„Special fitting design for tube cleaning applications up to 1.400 bar / 20.300 psi“

Key Features

- Visibly shorter than standard fittings
> easier cleaning of elbows
- Minimum OD of sleeve to meet customer requirements
> use of hoses with higher flow

BLAST-PRO® END-FITTING



„Special fitting design for tube cleaning applications up to 1.800 bar / 26.100 psi“

Key Features

- High-tensile stainless steel
- Visibly shorter than standard fittings
> easier cleaning of elbows
- Minimum OD of sleeve to meet customer requirements
> use of hoses with higher flow



„Special fitting design for tube cleaning applications up to 2.800 bar / 40.600 psi“
StoneAge® BANSHEE®

Key Features

- Visibly shorter & slimmer end-fitting design
> more efficient tube cleaning
- 100% seamless design to nozzle
> no need of adapters
- Available with HP 1/4" & HP 3/8" connections

ACCESSORIES

The accessories complement your hose assembly and provide increased safety and service life

1. **Protection Hose:** abrasive protection
2. **Bend Restrictor:** prevents „buckling“ and tensioning of the hose, adjusted to hose assembly
3. **Hose Securing Grip:** secures high-pressure hoses which are connected to the pump or aggregate - prevent whipping of the hose assemblies in case of hose failure
4. **Adapters and Tubing:** complement your assembly with various connection combinations: adapters, elbows, tees, crosses and tubing
5. **Stop Sleeves and Marking Rings:** relevant safety item for automated and manual cleaning for Waterblast standards



Product Overview - Waterblasting

HIGH PRESSURE PERFORMANCE

Type	Hose Size				Pressure Rating				Bend Radius		Weight		Insert ID		Sleeve OD	
	ID [mm]	[in]	OD [mm]	[in]	Working [bar]	[psi]	Burst [bar]	[psi]	[mm]	[in]	[kg/m]	[lbs/ft]	[mm]	[in]	[mm]	[in]

Tank Cleaning up to 2.500 bar / 36.250 psi

Application: Tank and vessel cleaning, cleaning with booms

8/6H	7,7	0,30	18,8	0,74	2.500	36.250	6.250	90.625	260	10,24	0,925	0,620	4,5	0,18	22,8	0,90
13/4H	12,8	0,50	22,0	0,87	1.400	20.300	3.500	50.750	200	7,87	0,880	0,590	7,5	0,30	29,5	1,16

Surface Preparation up to 4.000 bar / 58.000 psi

Application: Concrete removal, surface cleaning, paint removal, cleaning with hydro mowers, hand-held surface cleaner or hand guns

4/4UHP-X-3035	4,0	0,16	9,9	0,39	3.035	44.000	6.100	88.450	90	3,54	0,234	0,157	2,5	0,10	14,7	0,58
5/6H	4,6	0,18	14,4	0,57	2.800	40.600	7.000	101.500	220	8,66	0,563	0,377	2,5	0,10	17,9	0,70
5/6HDC I	4,6	0,18	18,4	0,72	2.800	40.600	7.000	101.500	220	8,66	0,687	0,460	2,5	0,10	17,9	0,70
5/6UHP-X-3035	4,8	0,19	13,3	0,52	3.035	44.000	7.000	101.500	210	8,27	0,450	0,302	2,5	0,10	17,8	0,91
5mmUHP	4,5	0,18	15,3	0,60	3.200	46.400	8.000	116.000	250	9,84	0,693	0,464	2,5	0,10	19,7	0,77
5mmUHP-X	4,5	0,18	15,3	0,60	4.000	58.000	8.000	116.000	250	9,84	0,693	0,464	2,5	0,10	19,7	0,77
6mmUHP	5,8	0,23	18,6	0,73	3.200	46.400	8.000	116.000	280	11,02	1,060	0,710	3,0	0,12	23,7	0,93
8/6H	7,7	0,30	18,8	0,74	2.500	36.250	6.250	90.625	260	10,24	0,925	0,620	4,5	0,18	22,8	0,90
8/6HDC I	7,7	0,30	22,8	0,90	2.500	36.250	6.250	90.625	260	10,24	1,085	0,727	4,5	0,18	22,8	0,90
8/6UHP	7,6	0,30	19,3	0,76	2.800	40.600	7.000	101.500	300	11,81	1,055	0,707	4,5	0,18	23,7	0,93
8/6UHP-X	7,6	0,30	19,3	0,76	3.035	44.000	7.000	101.500	300	11,81	1,055	0,707	4,5	0,18	23,7	0,93
10mmUHP-X-3035	9,8	0,39	24,0	0,94	3.035	44.000	6.100	88.450	320	12,60	1,730	1,163	6,0	0,24	31,0	1,22
13/2WR	12,8	0,50	22,2	0,87	1.040	15.080	2.600	37.700	150	5,91	0,590	0,395	7,5	0,30	27,5	1,08
13/4H	12,8	0,50	22,0	0,87	1.400	20.300	3.500	50.750	200	7,87	0,880	0,590	7,5	0,30	29,5	1,16
13mmUHP	12,8	0,50	27,7	1,09	2.800	40.600	6.000	87.000	350	13,78	2,085	1,397	7,5	0,30	34,6	1,36
16mmUHP	15,9	0,63	31,8	1,25	2.000	29.000	5.000	72.500	400	15,75	2,523	1,690	10,5	0,41	38,0	1,49
20/6	18,8	0,74	32,8	1,29	1.400	20.300	3.500	50.750	350	13,78	2,170	1,454	13,0	0,51	42,9	1,68
20/6-1600	18,8	0,74	32,8	1,29	1.600	23.200	4.000	58.000	350	13,78	2,170	1,454	13,0	0,51	42,9	1,68
25/6	24,8	0,98	39,8	1,57	1.400	20.300	3.000	43.500	600	23,62	2,800	1,876	17,5	0,69	49,0	1,92

Cutting and Demolition up to 3.200 bar / 46.400 psi

Application: Cutting and demolition of armoured concrete, pipelines, paper or steel, cleaning with hand guns, cutting systems

3/4	3,4	0,13	8,0	0,31	2.000	29.000	5.000	72.500	110	4,33	0,135	0,090	2,0	0,08	12,1	0,47
3/4-2100	3,4	0,13	8,1	0,32	2.100	30.450	5.250	76.215	110	4,33	0,135	0,090	2,0	0,08	12,1	0,47
3/6	3,0	0,12	9,1	0,36	2.800	40.600	7.000	101.500	150	5,91	0,222	0,149	1,8	0,07	15,3	0,60
4/6	4,0	0,16	11,5	0,45	2.800	40.600	7.000	101.500	175	6,89	0,365	0,245	1,8	0,07	17,1	0,67
4/8	4,0	0,16	12,8	0,50	3.200	46.400	8.000	116.000	175	6,89	0,540	0,362	1,8	0,07	19,5	0,76
8/6H	7,7	0,30	18,8	0,74	2.500	36.250	6.250	90.625	260	10,24	0,925	0,620	4,5	0,18	22,8	0,90
8/6HDC I	7,7	0,30	22,8	0,90	2.500	36.250	6.250	90.625	260	10,24	1,085	0,727	4,5	0,18	22,8	0,90
13mmUHP	12,8	0,50	27,7	1,09	2.800	40.600	6.000	87.000	350	13,78	2,085	1,397	7,5	0,30	34,6	1,36
20/6	18,8	0,74	32,8	1,29	1.400	20.300	3.500	50.750	350	13,78	2,170	1,454	13,0	0,51	42,9	1,68
20/6-1600	18,8	0,74	32,8	1,29	1.600	23.200	4.000	58.000	350	13,78	2,170	1,454	13,0	0,51	42,9	1,68



FRANKREICH
SPIR STAR® FRANCE SAS

67500 Haguenau
+33 (0) 388-9322 23
spirstar@spirstar.fr



USA
SPIR STAR® Ltd.

Houston, Texas, 77064
+1 (0) 281-664 7800
info@spirstar.com



DEUTSCHLAND

Headquarters
SPIR STAR® AG
64668 Rimbach (Mitlechtern)
+49 (0) 6253-9889 0
info@spirstar.de



ASIEN
SPIR STAR® ASIA PTE Ltd.

Singapore, 628833
+65 (0) 6-265 3011



CHINA
SPIR STAR® CHINA Co., Ltd.

Shanghai, 201108
+86 (0) 21-3463 5159

