

# DERC Speed Regulated Line Cleaner SLC

## DERC Speed Regulated Line Cleaner SLC

Scan for more info



### VERSATILE MODULAR PIPE CLEANING TOOL

The rotation speed of this modular pipe cleaning tool can easily be adjusted "manually" for the required cleaning job. Slow speeds for plugged pipes with hard residues, and fast speeds for polishing the inner walls of the pipes.

#### Cleaning Heads

To suit the requirements of every cleaning job the SLC has a variety of head choices available to which you can connect a pulling ring, customized ports and have multiple jetting options. The SLC heads are based on pressure, flow and type of cleaning work.

#### Extension Lances

Certain head options require extension nipples. See our extension lances for the possibilities.

#### FEATURES

- Up to 1500 bar
- Manual speed adjustment
- Choose the right SLC head for the job
- Optional pulling ring
- Optional extension lances
- Rugged stainless steel construction

#### APPLICATIONS

- Cleaning plugged pipes with hard residues
- Polishing inner walls of pipes



#### SLC OPTIONS

	SLC-1000	SLC-1500
<b>Inlet Connection</b>	3/4"NPT F	M24 x 1.5 Flat F 3/4" or 14 NPS F (3/4 MP)
<b>Shaft Connection</b>	3/4"NPT M	M24 x 1.5 Flat M
<b>Max. Pressure</b>	1000 bar	1500 bar
<b>Diameter</b>	75 mm	75 mm
<b>Length</b>	155 mm	175 mm
<b>Max. Flow</b>	380 lpm	380 lpm
<b>Part No.</b>	SLC-1000-34NF.34NM	SLC-1500-24FV.24MR, SLC-1500-M12F.24MR

#### Accessories

The DERC Salotech centralizers allow the SLC to work seamlessly with our high pressure extension arms, placing the effective water jets closer to the wall of the pipe. In addition the jetting configurations can easily be optimized with our high quality DERC Salotech inserts, to provide either more pulling power or more unplugging power.

## DERC Speed Regulated Line Cleaner SLC

## DERC Speed Regulated Line Cleaner SLC

Scan for more info



SLC HEAD OPTIONS						
	SLC-56-12NF	SLC-56-14NF	SLC-57-14NF	SLC-66-14NF	SLC-66-34UF	SLC-67-14NF
<b>Off Set</b>	3, 5, 9, 15	3, 5, 9, 15	3, 5, 9, 15	3, 5, 9, 12, 15	5, 9, 12, 15	3, 5, 9, 15
<b>Max. Pressure</b>	1000 bar	1000 bar	1000 bar	1500 bar	1500 bar	1500 bar
<b>Connection</b>	6x 1/2" NPT	6x 1/4" NPT	7x 1/4" NPT	6x 1/4" NPT	6x 3/4" UNF	7x 1/4" NPT
<b>Jet Angle</b>	2x 45°, 2x 90° 2x 135°	2x 45°, 2x 90° 2x 135°	1x 15°, 2x 45° 2x 90°, 2x 135°	2x 45°, 2x 90° 2x 135°	2x 45°, 2x 90° 2x 135°	2x 15°, 2x 45° 2x 90°, 2x 135°
<b>Extension Lance</b>	SLC-56-EXT-xxx	-	-	-	SLC-66-EXT-xxx	-
<b>Pulling Ring</b>	SLC-90	SLC-90	-	SLC-90	SLC-90	-



SLC EXTENSION LANCES		
SLC-1000	TOTAL WIDTH 90 GR	TOTAL WIDTH 45 GR
SLC-56-EXT-050	190	146
SLC-56-EXT-075	240	181
SLC-56-EXT-100	290	217
SLC-56-EXT-150	390	287
SLC-56-EXT-200	490	358
SLC-56-EXT-250	590	428
SLC-56-EXT-300	690	499
SLC-56-EXT-350	790	569
SLC-56-EXT-400	890	640
SLC-1500	TOTAL WIDTH 90 GR	TOTAL WIDTH 45 GR
SLC-66-EXT-050	182	140
SLC-66-EXT-075	232	175
SLC-66-EXT-100	282	210
SLC-66-EXT-150	382	281
SLC-66-EXT-200	482	351
SLC-66-EXT-250	582	422
SLC-66-EXT-300	682	492
SLC-66-EXT-350	782	563



CALL US +31 186 - 62 14 84