



## **DERC DPT-Nozzle**

## FOR CLEANING HARD PLUGGED TUBES UP TO 1500 BAR

- + INNOVATIVE DESIGN
- + SHORT DELIVERY TIME
- + CONFIGURED ON REQUEST
- + MAX. WORKING PRESSURE 1500 BAR





DERC Salotech T +31 186 62 14 84 info@salotech.nl www.salotech.nl

Jan van der Heijdenstraat 44 3261 LE Oud-Beijerland The Netherlands

# **DERC DPT-Nozzle**

## FOR CLEANING HARD PLUGGED TUBES UP TO 1500 BAR

The DERC Piramid Type (DPT-nozzle) is designed for cleaning hard plugged tubes with a maximum pressure of 1500 bar/22K. The nozzle is protected against mechanical damage because the nozzle-holes are drilled in a groove of the nozzle-body.

### **INNOVATIVE DESIGN**

The innovative design gives the DPT-nozzle an optimal flow, better results and a longer life cycle. The DPT-nozzle is available in three diameters. The nozzle-body is corrosion resistant, hardened and guarantees a long life cycle.The nozzle will be configured and drilled for the job or according customer specifications.

### STOCK ITEM

The DPT-nozzle is a stock item with a short delivery time and an attractive price level.

#### **CONFIGURED ON REQUEST**

The nozzle will be optimally configured for your working conditions. Based on your requirements and specifications (such as pressure, pump capacity, use as pulling/ pushing or neutral, connection, thread, permissible reaction force and spray pattern) we can advise you on the optimal configuration.



DERC DPT-NOZZLE				
CONNECTION	THREAD	LENGTH	DIAMETER	PART NO.
M7x1	Female	28 mm	Ø 10 mm	DPT.07F.xxx
1/8" BSP	Female	31.5 mm	Ø 12 mm	DPT-18F.xxx
1/4" BSP	Female	36 mm	Ø16mm	DPT-14F.xxx