

DERC DPT-Nozzle

DERC DPT-Nozzle



FOR CLEANING HARD PLUGGED TUBES UP TO 1500 BAR

The DERC Piramid Type (DPT-nozzle) is designed for cleaning hard plugged tubes with a maximum pressure of 1500 bar/ 22K. The nozzle is protected against mechanical damage because the nozzle-holes are drilled in a groove of the nozzle body.

Innovative Design

The DPT-nozzle is available in three diameters. The nozzle body is corrosion resistant, hardened and guarantees a long life cycle.

Stock Item

The DPT-nozzle is a stock item with a short delivery time and an attractive price level.

Configured on Request

The nozzle will be optimally configured for your working conditions based on your requirements and specifications (such as pressure, pump capacity, use as pulling/pushing or neutral, connection, thread, permissible reaction force and spray pattern).

FEATURES

- Up to 1500 bar
- Configured on request
- Short delivery times

APPLICATION

- For cleaning hard plugged tubes

DERC DPT-NOZZLE

Connection	M/F	Length	Diameter	Max. Pressure	Part No.
M7x1	Female	28 mm	Ø 10 mm	?	DPT.07F.xxx
1/8" BSP	Female	31,5 mm	Ø 12 mm	?	DPT-18F.xxx
1/4" BSP	Female	36 mm	Ø 16 mm	?	DPT-14F.xxx

NOZZLE JET ANGLES*

B1	0,0°
B2	15,0°
B3	30,0°
B4	45,0°
B5	100,0°
B6	105,0°
B7	135,0°

**Applicable to: DPT-07F, DPT-14F & DPT-18F nozzle types*

