

DERC DST-Nozzle

DERC DST-Nozzle

Scan for
more info



FOR CLEANING BENDED TUBES UP TO 1500 BAR

The DERC Short Type (DST-nozzle) is designed for flex lancing around small radius bends to a maximum pressure of 1500 bar/ 22K. The nozzle is protected against mechanical damage because the nozzle holes are drilled in a groove of the nozzle body.

Innovative Design

The DST-nozzle is available in three diameters. The nozzle body is corrosion resistant, hardened and guarantees a long life cycle.

Stock Item

The DST-nozzle is a stock item with a short delivery time and an attractive price level.

Configured on Request

The nozzle will be optimally configured for your working conditions based on your requirements and specifications (such as pressure, pump capacity, use as pulling/pushing or neutral, connection, thread, permissible reaction force and spray pattern).

FEATURES

- Up to 1500 bar
- Configured on request
- Short delivery times

APPLICATION

- For cleaning bended tubes

DERC DST-NOZZLE

Connection	M/F	Length	Diameter	Max. Pressure	Part No.
M7x1	Female	16 mm	Ø 10 mm	?	DST-07F.xxx
1/8" BSP	Female	19 mm	Ø 12 mm	?	DST-18F.xxx
1/4" BSP	Female	24 mm	Ø 16 mm	?	DST-14F.xxx

NOZZLE JET ANGLES*

B1	0,0°
B2	45,0°
B3	90,0°
B4	135,0°

**Applicable to: DST-07F, DST-14F & DST-18F nozzle types*

