



DERC DST-Nozzle

FOR CLEANING BENDED TUBES UP TO 1500 BAR

- + INNOVATIVE DESIGN
- + SHORT DELIVERY TIME
- + CONFIGURED ON REQUEST
- + MAX. WORKING PRESSURE 1500 BAR



DERC Salotech

T +31 186 62 14 84 info@salotech.nl www.salotech.nl

Jan van der Heijdenstraat 44 3261 LE Oud-Beijerland The Netherlands

DERC DST-Nozzle

FOR CLEANING BENDED TUBES UP TO 1500 BAR

The DERC Short Type (DST-nozzle) is designed for flex lancing around small radius bends to a maximum pressure of 1500 bar/ 22K. The nozzle is protected against mechanical damage because the nozzle-holes are drilled in a groove of the nozzle-body.

INNOVATIVE DESIGN

The innovative design gives the DST-nozzle an optimal flow, better results and a longer life cycle. The DST-nozzle is available in three diameters. The nozzle-body is corrosion resistant, hardened and guarantees a long life cycle. The nozzle will be configured and drilled for the job or according customer specifications.

STOCK ITEM

The DST-nozzle is a stock item with a short delivery time and an attractive price level.

CONFIGURED ON REQUEST

The nozzle will be optimally configured for your working conditions. Based on your requirements and specifications (such as pressure, pump capacity, use as pulling/pushing or neutral, connection, thread, permissible reaction force and spray pattern) we can advise you on the optimal configuration.



DERC DST-NOZZLE				
CONNECTION	THREAD	LENGTH	DIAMETER	PART NO.
M7x1	Female	16 mm	Ø 10 mm	DST.07F.xxx
1/8" BSP	Female	19 mm	Ø 12 mm	DST-18F.xxx
1/4" BSP	Female	24 mm	Ø 16 mm	DST-14F.xxx

DERC SALOTECH – ORIGINAL EQUIPMENT MANUFACTURER AND SUPPLIER OF INNOVATIVE HIGH PRESSURE WATER JETTING SOLUTIONS, AUTOMATED EQUIPMENT AND ACCESSORIES. WE PROVIDE STATE OF THE ART KNOWLEDGE AND SERVICES.