



DERC DTLX-Nozzle

FOR (RIGID) LANCES AND LANCING MACHINES UP TO 1500 BAR

- + INNOVATIVE DESIGN
- + SHORT DELIVERY TIME
- + CONFIGURED ON REQUEST
- + MAX. WORKING PRESSURE 1500 BAR



DERC Salotech

T+31 186 62 14 84 info@salotech.nl www.salotech.nl

Jan van der Heijdenstraat 44 3261 LE Oud-Beijerland The Netherlands

DERC DTLX-Nozzle

FOR CLEANING WITH (FLEX) LANCES UP TO 1500 BAR

The DERC DTLX-nozzle is specially designed for cleaning with (flex) lances, up to a maximum pressure of 1500 bar/ 22K. The nozzle is protected against mechanical damage because the nozzle-holes are drilled in a groove of the nozzle-body.

INNOVATIVE DESIGN

The innovative design gives the DTLX-nozzle an optimal flow, better results and a longer life cycle. The DTLX-nozzle is available in three different diameters. The nozzle-body is corrosion resistant, hardened and guarantees a long life cycle. The nozzle will be configured and drilled for the job or according customer specifications.

CONFIGURED ON REQUEST

The nozzle will be optimally configured for your working conditions. Based on your requirements and specifications (such as pressure, pump capacity, use as pulling/pushing or neutral, connection, thread, permissible reaction force and spray pattern) we can advise you on the optimal configuration.



DERC DTLX-NOZZLE				
CONNECTION	THREAD	LENGTH	DIAMETER	PART NO.
1/4" UNF LH	Female	27 mm	Ø 9.5 mm	DTLX-14MFL.xxx
3/8" UNF LH	Female	35 mm	Ø 13 mm	DTLX-38MFL.xxx
9/16" UNF LH	Female	42 mm	Ø 18 mm	DTLX-916MFL.xx

DERC SALOTECH - ORIGINAL EQUIPMENT MANUFACTURER AND SUPPLIER OF INNOVATIVE HIGH PRESSURE WATER JETTING SOLUTIONS, AUTOMATED EQUIPMENT AND ACCESSORIES. WE PROVIDE STATE OF THE ART KNOWLEDGE AND SERVICES.