



DERC DUT-Nozzle

FOR (RIGID) LANCES AND LANCING MACHINES UP TO 1500 BAR

- + INNOVATIVE DESIGN
- + SHORT DELIVERY TIME
- + CONFIGURED ON REQUEST
- + MAX. WORKING PRESSURE 1500 BAR



DERC Salotech

T +31 186 62 14 84 info@salotech.nl www.salotech.nl

Jan van der Heijdenstraat 44 3261 LE Oud-Beijerland The Netherlands

DERC DUT-Nozzle

FOR (RIGID) LANCES AND LANCING MACHINES UP TO 1500 BAR

The DERC Universal Type (DUT-nozzle) is designed for rotating lances, flex lances and lancing machines to a maximum pressure of 1500 bar. The nozzle is protected against mechanical damage because the nozzle-holes are drilled in a groove of the nozzle-body.

INNOVATIVE DESIGN

The innovative design gives the DUT-nozzle an optimal flow, better results and a longer life cycle. The DUT-nozzle is available in four diameters. The nozzle-body is corrosion resistant, hardened and guarantees a long life cycle. The nozzle will be configured and drilled for the job or according to customer specifications.

STOCK ITEM

The DUT-nozzle is a stock item with a short delivery time and an attractive price level.

CONFIGURED ON REQUEST

The nozzle will be optimally configured for your working conditions. Based on your requirements and specifications (such as pressure, pump capacity, use as pulling/pushing or neutral, connection, thread, permissible reaction force and spray pattern) we can advise you on the optimal configuration.



DERC DUT-NOZZLE				
CONNECTION	THREAD	LENGTH	DIAMETER	PART NO.
M7x1	Female	27 mm	Ø 10 mm	DUT-07F.xxx
1/8" BSP	Female	30 mm	Ø 12 mm	DUT-18F.xxx
1/4" BSP	Female	35 mm	Ø 16 mm	DUT-14F.xxx
3/8" BSP	Female	46 mm	Ø 22 mm	DUT-38F.xxx

DERC SALOTECH – ORIGINAL EQUIPMENT MANUFACTURER AND SUPPLIER OF INNOVATIVE HIGH PRESSURE WATER JETTING SOLUTIONS, AUTOMATED EQUIPMENT AND ACCESSORIES. WE PROVIDE STATE OF THE ART KNOWLEDGE AND SERVICES.